


ELECTRICAL POWER SUPPLY: 24[Vdc] +/- 5%
 4x CONNECTOR M8 MALE, 3 POLES:
 - PIN 1(BROWN): +24[Vdc]
 - PIN 3(BLUE): 0[Vdc]
 - PIN 4(BLACK): PWM-CONTROL

PWM CONTROL PIN CONNECTION:
 - +24[Vdc]: ILLUMINATOR ON
 - 0[Vdc]: ILLUMINATOR OFF



PAY ATTENTION:
 install the illuminator so that the bottom wall is in direct contact with a flat metal surface. In this way the support surface of the illuminator will be able to guarantee an adequate dissipation of the heat produced by the LEDs. Maintaining a low illuminator temperature allows the average life of the LEDs to be lengthened and the light emission to remain stable.

3.2 [Symbol] Undimensioned chamfers 0.5x45°

Revisions			
Rev.	Description	Date	Slip.

General machining tolerances: H11 hole - h11 shaft - linear dimensions ±0.1mm - angular values ±30'		Surface texture according to UNI 9600-83, unless otherwise specified. Geometrical tolerances according to UNI 7226-1.	
	Product	BL3	Group
	Initial revision date (0)	17/06/2026	Designer
Material	Scale	1:2	Format
Treatment	Quantity	1	Table N/N
Description	Drawing number	BL3-400x400	1/1
<small>Property of RODER s.p.a. - Via Sissa Nuova 15A - 10080 - Ogliastro (TO) - ITALY - Copyright by RODER s.p.a. - All rights reserved. Without written authorization from RODER s.p.a., this drawing may not be used for the manufacturing of the object represented herein, nor disclosed to third parties. The owner company will protect its rights to the full extent of the law. Unauthorized use of the content of this document constitutes a criminal and civil offense.</small>			